



ANCILLARY

www.AsaFire.ir

Your Safety, Our Technology

YBD-RA

Surface Wiring Adaptor

Features

- Compatible with the majority of existing Analogue and Conventional bases
- Colour matches standard Hochiki Analogue and Conventional sensor/detector/base ranges
- 4 pre-moulded knock-outs provide wiring entry
- Low profile - only 16mm.



Description

The YBD-RA Surface Wiring Adaptor allows the majority of Hochiki Sensors/ Detectors and their Mounting Bases to be fitted flush against a fixing surface whilst also allowing surface wiring (without conduit) to be connected.

The adaptor features four 9mm x 8mm knock-outs for cables/wires allowing surface fixed wiring to be connected to an appropriate mounting base (depending on application).

The adaptor is moulded in ivory white ABS as standard, which allows seamless integration with the majority of mounting bases and associated sensors and detectors.

Specification

Ordering codes	YBD-RA - Ivory / YBD-RA(WHT) - White
Maximum humidity	95% RH - Non Condensing (at 40°C)
Operating Temperature Range	-20 °C to +70 °C
Colour	Ivory or White
Weight (g) / Dimensions (mm)	27 / Ø 110 x H 16
Fixing centres (mm)	61 ~ 89
Maximum wire thickness	2.5mm ² cables



For further information visit our website.
Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.