

CCP-KS

Conventional Key Switch Manual Call Point

Features

- ▶ Approved to EN54-11:2001
- ▶ Two position keyswitch (marked “1” and “0”) with key removable in both positions
- ▶ Terminals can accommodate up to a 2.5 mm² solid conductor
- ▶ Supplied in RED - other colours available on request
- ▶ Supplied with back box for surface fixing
- ▶ Suitable for fire, security and other specialist applications
- ▶ Approved by LPCB.



Description

The CCP-KS is a Conventional key switch manual call-point based upon the industry standard KAC 9000 series housing and features flying leads for simple wiring.

The unit features two key positions marked as “1” and “0” – with the key easily removable in either position.

Specification

Ordering codes	CCP-KS
Maximum voltage	24 VDC or 24 VAC
Current rating	6 A @ 240 VDC / 2 A @ 240 VAC
IP rating	IP24D
Operating / Storage temperature range	- 20 °C to + 55 °C
Maximum Humidity	95% RH - non-condensing (at 40°C)
Colour / Case Material	Red / ABS
Weight (g) / Diameter (mm) / Height (mm)	180 / W 87 x H 87 x D 52



For further information visit our website.
 Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.