

CSBB-E

Conventional Sounder Base Beacon

Features

- ▶ Robust design
- ▶ Low current consumption
- ▶ Easy to install
- ▶ Maximum 93 dB(A) @ 1 metre (Tone 1)
- ▶ 32 user-selectable tones and 3 userselectable volumes
- ▶ Utilises high intensity LEDs
- ▶ Lockable cap available.



Description

The CSBB-E is platform type sounder beacon, which will accept the CDX Range of detectors mounted with an appropriate base*. The improved electronics result in a very low current consumption with a high sound output. A set of DIL switches are used to select the unit's tone and sound output (three settings, LOW, MEDIUM and HIGH). Advanced LED technology provides a high intensity flash.

Specification

Ordering codes	CSBB-E - Ivory / CSBB-E(WHT) - White / CS-CAP - Lockable cap		
Sound level	LOW	MEDIUM	HIGH
Sound output @ 1 metre: Tone 1	87 dB(A)	90 dB(A)	93 dB(A)
Current consumption @ 24 VDC	8 mA	9.3 mA	11.5 mA
Operating Voltage	18 – 30 VDC		
Number of tones	32		
Operating frequency	440 - 2900 Hz		
IP rating	IP42		
Operating Temperature Range	-20 °C to +70 °C		
*Compatible CDX Bases	YBN-R/6, YBO-R/6PA, YBO-R/6R, YBO-R/6RN, YBO-R/6RS, YBN-R/6SK		
Compatible CDX Detectors	SLR-E3N, DCD-AE3, DCD-CE3, DFJ-AE3, DFJ-CE3		
Colour / Case Material	Ivory or White / ABS		
Weight (g) / Diameter (mm) / Height (mm)	110 / 116 / 25		