

SMB-3

DIN Module Enclosure

Features

- Designed to house up to 4 Hochiki DIN Modules
- Quick-release screws
- Polyurethane gasket provides IP66 protection
- Corrosion free, resistant to most alkaline and acid
- Temperature resistance to +70°C, Impact resistant, and Non-flammable
- 20 knock-outs
- Supplied with DIN Rail and fixings.



Fitted enclosure as example

Description

Model SMB-3 is from a range of IP66 rated, grey (RAL7035) enclosures, designed for use with the Hochiki range of DIN Modules. The SMB-3 features a selection of metric knockouts and is supplied with a transparent black lid as standard; an opaque lid is also available (sold separately).

The unit is supplied with a DIN Rail section (plus fixings) and will accept up to four Hochiki DIN Rail Modules, side-by-side.

Specification

Ordering codes	SMB-3 - Base and transparent lid		SMB-3(LID) - Opaque lid
IP rating	IP66		n/a
Colour	Box - Grey (RAL7035) Lid - Transparent black		Grey (RAL7035)
Material	Box - Polystyrene Lid - Polycarbonate		Polystyrene
Weight (g)	575		300
Dimensions (mm) DIN Dimensions (mm)	L 180 x W 110 x H 165 L 100 x W 35 ('top hat')		L 180 x W 110 x H 92 n/a
Knock-out configuration	Long sides	1 x M32/40 4 x M20	n/a
	Short sides	1 x M32/40 4 x M20	
Suitable protection against	Weak alkali, strong alkali, alcohol, petrol, benzene, mineral oil, diesel, ammonia, vegetable oil, animal oil		

FASTENER INFORMATION:

For Mounting plate (always required) - 4 x M3 CTSK Self Tapper

For CHQ Module PCB - 2 x M4 Pan Head Screws + 2 split washers

For 'mini' CHQ - 2 x M3 CTSK Machine Screws

For DIN Rail washers - 2 x M3 Pan Head Machine Screws + 2 splits



For further information visit our website. Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.

