

## Conventional MCP compact, small, red, with glass pane, IP 66/67

**Part-No.: 804960****Approval: VdS**

Waterproof MCP including housing and alarm indicator. For connection to a conventional detection zone.

**Common technical data**

Operating voltage	8 ... 30 V DC
Quiescent current @ 9 V DC	0 µA
Alarm current @ 9 V DC	9 mA
No. of detector/zone	10 detectors per zone (according to VdS)
Alarm display	red LED and yellow actuation indicator
Connection terminal	max. 2.5 mm <sup>2</sup> (AWG 26-14)
Application temperature	-40 °C ... 70 °C
Storage temperature	-40 °C ... 75 °C
Air humidity	< 95 %
Type of protection	IP 66 / IP 67
Housing	PC ASA plastic
Color	red, similar to RAL 3020
Weight	approx. 110 g
Detector specification	EN 54-11, type A
Dimensions	W: 88 mm H: 88 mm D: 21 mm

**Features:**

- High IP protection class IP 66 / 67
- Integrated loop isolator
- Triple key function (test, open, reset)
- Plug-in connection clamps
- Detectors that are not ready for operation can be marked with the "out of order" label by reversing the enclosed glass pane

 Use M20 cable glands with 15 mm connecting thread length and sealing ring, e.g. blueglobe by Pflitsch (Screw joint Part No.: bg 820PA/sealing ring part no.: DRF 220).

 1 x Spare glass 704960 1 x Plastic spare key 704966 1 x Transparent cover 1 x Surface mount housing